

NV200 Specifications

The NV200 is suitable for smaller shared office spaces or individual rooms in a house or hotel. It can be placed on a countertop, stand-alone or mounted on a wall. It processes 80m3/hr (cubic metres of air an hour).

NOVAERUS uses patented active purification technology to continuously pull contaminated indoor air across internal short-exposure plasma coils, deactivating airborne microorganisms and viruses at the DNA level.

MODEL

NOVAERUS NV200 Air Purifier Wall mountable, countertop or stand-alone unit supplied with 2m power cord

ELECTRICAL RATING

230 VAC, 50 Hz Single Phase, 20 W Fuse rated at 250 VAC, 3 Amps, Listed Power consumption 20 Watts

CONSTRUCTION + COLOR

Precision cut fabricated metal casing in a white anti-bacterial powder coat finish.

DIMENSIONS + WEIGHT

28.3 (h) x 13.2 (w) x 10.8 (d) cm 3.4kg

ELECTRICAL CONNECTION

Switched and fused with a grounded, molded power cord.

FAN AIR FLOW VOLUME 80 m³/hr

NOISE LEVEL 35 dB

OPERATING CONDITIONS 10°-35°C, 10-75% Relative Humidity, 2000m

SHIPPING / STORAGE CONDITIONS 5°-50°C, Maximum 95% Relative Humidity

QUALITY + SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001

Click Here to Request a Quote



